


ITEM	PART NAME	MATERIAL	QTY
1	UPPER STEM	MONEL R405	1
2	PACKING RING	VIRGIN TEFLON	1
3	HANDLE NUT	ASB	1
4	HANDLE	BRASS	1
5	BONNET	ASB	1
6	THRUST BEARING	VIRGIN TEFLON	1
7	PACKING FOLLOWER	ASB	1
8	PACKING NUT	ASB	1
9	DISC SPRING	PH SST	3
10	SPRING	316 SST	1
11	LOWER STEM ASSY.	MONEL/KEL-F	1
12	BODY	316 SST	1
13	RING	BRASS	1
14	PACKING	TEFLON	1



UNCONTROLLED
For Reference Only
MB 3/30/2007

SPECIFICATIONS:
PRESSURE RATING: 3500 PSI
FLOW COEFFICIENT $C_v = 3.5$
SEAT ORIFICE SIZE: .50 ϕ
SEAT MATERIAL: KEL-F
TEMPERATURE LIMITS: -65° F TO 150° F
LEAK RATE: 1x10-3 ATM CC/SEC N2

GasFlo Products Inc.
Fairfield, N.J.

SALES DWG.- 3/4 FEMALE NPT x 3/4 FEMALE NPT
PRESSURE SEAL VALVE

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY AND CONFIDENTIAL PROPERTY OF GASFLO PRODUCTS INC. AND MAY BE USED ONLY FOR AUTHORIZED PURPOSES.
THIS DOCUMENT MAY NOT BE REPRODUCED WITHOUT GASFLO PRODUCTS INC. PRIOR WRITTEN CONSENT

DWN MB SCALE: NTS
APPVD DATE 10/19/05

DWG SALES-VLV-PS-1212SS-FF